data sheet



injectors





IS-300/60 linear (P)

pickle injector

Art.no. red meat 011451 Art.no. poultry 011460

meat: red meat, poultry

capacity: up to 6.000 kg/h* and 1.700 pc/h*

(details are based on minimum injection quantity and maximum forward)

injection amount: up to 80 %*

needles: 15 pc 2fold needles 4 mm and 3 mm

product description pickle injector "IS-300/60 linear"

with linear drive (needle return point freely selectable)

New Twist System

with synthetic conveyor belt

technical data

control VSP, ISC-B5 with 99 programs

poultry set for poultry version stripper stop and guiding rails

to assure a controlled product transport

working width 300 mm

clearance 50-220 mm

number of strokes per minute 5-50 strokes per minute speed of conveyor mm per stroke 30 or 60 mm per stroke

pump rotary pump power 2,2 kW

pressure approx. 1,0-2,5 bar

needle system red meat with 15 pc 2fold needles 4 mm ø 25B

poultry with 15 pc 2fold needles 3 mm ϕ 25B

(optional 4fold needles)

voltage 3 x 400 V / 50 Hz (other voltage on request)

total power requirements approx. 4,3 kW

dimensions machine

length: 1.703 mm width: 927 mm height: 1.950 mm

machine weight approx. 300 kg